



## **RIGEL 1020 LEATHER SIP FO SRC TECHNICAL DATASHEET**

Certification: ISO 20345:2011

Category: S1P FO SRC

Toecap: Composite toecap (200 Joule)

Upper: 1.8.-2.0 mm grain cow leather with

3D Air panels for maximum airflow.

Lining: 100% breathable 3D Air

Insole: R/Flow® insole

Anti Perforation: K18 kevlar midsole (1100N)
Outsole: PU/PU dual density, reflective, SRC

Available Sizes: 35-48 (EU)





















- √ High Abrasion Resistance Ensures long-lasting durability.
- ✓ Shock-Absorbing & Comfortable Offers all-day comfort.
- ☑ Lightweight & Flexible Reduces foot fatigue.
- ✓ Chemical & Oil Resistance Ideal for tough working conditions.
- √ Superior Slip Resistance Designed to meet SRC standards



- Figonomic Design Follows the natural shape of the foot for optimal support.
- ✓ Cushioned Heel Zone Reduces pressure and impact on the heel during long work shifts.
- ✓ All-Day Comfort Enhances overall foot comfort and reduces fatigue.
- ✓ Breathable & Antibacterial Helps keep feet dry and odor-free.



- ✓ Maximum Impact Protection Withstands up to 200 Joules of force.
- ✓ Industry Standard Certified under EN ISO 20345 steel toe requirements.
- ✓ Crush & Compression Resistant Prevents serious foot injuries.
- ✓ Reliable in Extreme Conditions Performs consistently in heat, cold, and high-pressure environments.



- ${f V}$  Superior Anti-Perforation Protects against sharp objects and nails.
- ✓ Durable Steel Construction Long-lasting and highly protective.
- Certified to EN ISO 20345 Ensures safety in hazardous ground conditions.
- Stable Foot Support Adds structure and protection to the